SOFTANE™ Tradition

JALASKA SAS J0266

S3 SRC EN ISO 20345:2011 36 to 48



Softane™ dual-density sole





- Natural-coloured boot with 2 leather side tabs for rapid pull-on.
- Upper in water and oil resistant full grain AP 23 leather, exclusive to :
 - C 10 to 15% thicker (2,4 mm) than most leathers used for safety footwear
 - Resistance to penetration of water vapour three times higher than the minimum fixed by european standard.
- Flat binding at top of quarters.
- Heel stiffener to reinforce the heel seat.
- Full-size inlay, removable, anti-bacterial treated, anatomical and comprising heel shock absorber. High
 capacity to absorb and desorb perspiration.
- Forefoot lining, resistant to abrasion and perspiration acids.
- Perforated steel toe-cap (patented) 200 J.
- Puncture-resistant stainless steel midsole.
- Dual density Softane™ sole with progressive shock absorber to protect back and joints from vibrations. Self cleaning sole pattern. Multi-directional treads. Rounded heel pressure zone for comfort and stability

Slip resistance tests results EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic/lubricant : water and detergent

On flat **0,58** (>0,32) – On the heel **0,54** (>0,28)

SRB Test ground steel/lubricant: glycerine
On flat 0,37 (>0,18) – On the heel: 0,14 (>0,13)

- ✓ Wraps round the foot for increased stability when walking.
- ✓ Outsole density = 1.02 / Comfort layer density = 0.45
- ✓ Highly resistant to oils and hydrocarbons.
- ✓ Abrasion resistance : 80 mm³
- ✓ Heel schock absorption 29 Joules.

Weight	Gross weight (42): 1740 g / Net weight (42): 1420 g
Sizes	36 au 48
Packaging	5 pairs
Dimensions (mm)	625 x 425 x 345





